



# DSI520 Enterprise Series

## Experience You Can Trust

Protecting the world's information is our mission. Offering 45+ years of experience in data protection solutions and expertise in both disk and tape technologies, DSI meets the needs of IT professionals worldwide. DSI offers optimized solutions for data backup, recovery and archiving. DSI has award winning designs, patented technologies, superior reliability, first class service and a variety of solutions customized to meet your needs.

## Maximize Use of Valuable Resources

The DSI520 Series Virtual Tape Library offers the most robust data protection for our customers. The DSI520-EV0 may be paired with any DSI qualified fibre-channel external storage in your environment, or the DSI520 series expansion modules, allowing expansion into the petabytes of backup capacity.

## Protect Your Investment

Data security is imperative when building a backup and disaster recovery solution. DSI utilizes the industry's top standards for at-rest and in-flight encryption to ensure that your data is never exposed to outside threats. The DSI520 ships standard with in-flight and at-rest encryption so your data is protected every step of the way.

## Maximize Your Data Center Efficiency

Data centers worldwide face the challenge of business critical data growing exponentially. The DSI520 Enterprise Series may be paired with deduplicating systems to insure maximum possible power, management and physical space efficiency. DSI also offers consulting services to assist with strategic backup and disaster recovery (DR) planning, design and implementation.

## Build Your Systems, Your Way

The DSI520 Series provides scalable, enterprise-class data protection available for any environment.

## Component Description for DSI520

DSI520-EV0: may be paired with any DSI qualified Fibre-Channel external storage in your environment, or the DSI520 Series expansion modules, allowing expansion into the petabytes of backup capacity.

DSI520-EVD: The enterprise deduplication module may be paired with either DSI's expansion modules or certified third-party disk arrays. No physical storage is included with the EVD head node.



See configuration table for details.

THE **DSI520** IS  
DESIGNED TO HELP  
YOU KEEP PACE  
WITH YOUR  
RAPIDLY  
EXPANDING DATA  
FOOTPRINT BY  
UTILIZING STATE-  
OF-THE-ART  
DEDUPLICATION.

The UNISYS logo is displayed in a bold, red, serif font. It is surrounded by a decorative graphic of interconnected hexagons and lines in a light green color, resembling a molecular or network structure.

Dynamic Solutions International  
373 Inverness Parkway  
Suite 110  
Englewood, CO 80112

Phone 303.754.2088  
Fax 303.754.2066  
DynamicSolutions.com

	 <b>DSI520-EV0</b>	 <b>DSI520-EVD</b>
	VTL Node	Deduplication Node
End user capacity	<b>Up to 3.8PB</b>	
	Enterprise VTL Node	Enterprise Deduplication Node
# virtual libraries	128	
# virtual tape drives	1,024	
# virtual tape cartridges supported	250,000	
Backend physical tape	FC only	
Replication (w/ encryption / compression)	Optional	
SecureTape encryption	Optional	
Tape consolidation (stacking)	Optional	
High Availability	Optional	N + 1 Option
Data De-duplication	Requires DSI520 EVD	Yes
VTL Agent	Optional	N/A
Open systems ISV attachment	Yes	Yes
DSI TapeManager / LibraryManager	Optional	N/A
Maximum Configuration (Cluster)	Up to 8 additional Nodes	Up to 4 additional Nodes
Processors	2 x Intel Xeon 4110	2 x Intel Xeon 4114
RAM	64 GB	384 GB
Form Factor	2U	2U
Number of GBe Ports	4	4
Number of FC Ports	12 (16 GB)	4 (16 GB) + 2 Optional
Number of SAS Input Ports	0	0
Number of SAS Output Ports	0	0
Internal storage capacity (usable)	800 GB (0)	800 GB (0)
# drives	2 x 400 GB - RAID 0	2 x 400 GB - RAID 0
Dimensions (H x W x D):	3.40" x 17.44" x 26.80"	3.40" x 17.44" x 26.80"
Weight:	57.54 lbs	57.54 lbs
Temperature / Humidity considerations:	10 - 35°C / 10 - 80%	10 - 35°C / 10 - 80%
Heat output / cooling requirements:	4,100 BTU's/hr	4,100 BTU's/hr
Power supply rating (self switching)	100 - 240v, 50/60hz	100 - 240v, 50/60hz
Power / breaker requirements - US / C	1,100w/110v/12a	1,100w/110v/12a
Power / breaker requirements - Int'l	1,100w/240v/6.5a	1,100w/240v/6.5a

Visit us at [DynamicSolutions.com](http://DynamicSolutions.com) or call **303.754.2088** to speak directly with a data management specialist.



**UNISYS**